

Housing: Vandal-resistant, self-extinguishing, UV-stabilized, anti-yellowing grey polycarbonate.

Diffuser: Vandal resistant, V2 self-extinguishing, UV-stabilised clear polycarbonate, anti-glare frosted inside; smooth, dust-proof outside.

Reflector: Reflecting white polycarbonate.

Electric gear: 230V-240/60Hz power supply with electronic ballast. 4P terminal block for SE version and 6P terminal block for SA version (maximum allowed lead cross-section 2.5 sqmm).

Equipment: rubber cable gland; fixture presetted for REST MODE function. Standard inspection LED.

S.A. Emergency (Maintained): In the event of a black-out the one lamp connected to the back-up circuit stays on, thus avoiding the inconvenience caused by a sudden absence of all light.

Emergency run time: 60/180 minutes. When power is restored, the battery recharges automatically in 12 hours.

S.E. Emergency (Only emergency): In the event of a black-out the one lamp connected to the back-up circuit ignites, thus avoiding the inconvenience caused by a sudden absence of all light. Emergency run time: 60/180 minutes. When power is restored, the battery recharges automatically in 12 hours.


610 Safety - only emergency 1h S.E.						
		CEM-L		Auto self-test		Lamps
wattage	colour	weight	code	weight	code	
FLC 18L	grey	1.00	112460-00	1.00	112460-0066	4000K - 1200lm
FLC 24L	grey	1.00	112461-00	1.00	112461-0066	4000K - 1800lm

611 Safety - emergency 1h S.A.						
		CELL-E		Auto self-test		Lamps
wattage	colour	weight	code	weight	code	
FLC 18L	grey	1.00	112470-00	1.00	112470-0066	4000K - 1200lm
FLC 24L	grey	1.00	112471-00	1.00	112471-0066	4000K - 1800lm


612 Safety - only emergency 3h S.E.						
		CEM-L		Auto self-test		Lamps
wattage	colour	weight	code	weight	code	
FLC 18L	grey	1.00	112480-00	1.00	112480-0066	4000K - 1200lm
FLC 24L	grey	1.00	112481-00	1.00	112481-0066	4000K - 1800lm

613 Safety - emergency 3h S.A.						
		CELL-E		Auto self-test		Lamps
wattage	colour	weight	code	weight	code	
FLC 18L	grey	1.00	112490-00	1.00	112490-0066	4000K - 1200lm
FLC 24L	grey	1.00	112491-00	1.00	112491-0066	4000K - 1800lm


Example of installation art. 610/611/612/613




Wall installation



Recessed box installation



Recessed installation



Standard-feature rubber cable gland