



Housing: in die-cast aluminium, black powder coating.

Diffuser: external tempered glass, 15 mm, resistant to thermal shock and mechanical stress up to 2000 kg.




1814 Quadro - Power LED

wattage	colour	CTL		Beam angle	W tot	temperature and load				LED (Ta=25°C)		
		weight	code			max T. on glass ta 25°	max T. on glass ta 15°	max load kg	Can be walked on	bears vehicle loads	K	ølm 350mA
3,5W LED white	stainless steel	12,00	530940-00	20°	31,5W	50°	40°	2000	OK	OK	4000	2358lm
3,5W LED blue	stainless steel	12,00	530940-71	20°	31,5W	50°	40°	2000	OK	OK		634,5lm
3,3W LED red	stainless steel	12,00	530940-72	20°	31,5W	50°	40°	2000	OK	OK		826,2lm
3,3W LED yellow	stainless steel	12,00	530940-73	20°	31,5W	50°	40°	2000	OK	OK		826,2lm
3,5W LED green	stainless steel	12,00	530940-74	20°	31,5W	50°	40°	2000	OK	OK		1818lm


Supplied with components box.

On request: version with RGB LED for operation in Master / Slave or DMX integrated.

Incorporated power supply 220-240V 50/60 Hz.



Life: 40000h (from -30° to +50° C - Ta=25°C).



1819 Quadro LED

wattage 24V	colour	CLD CTL		W tot	temperature and load				LED (Ta=25°C)		
		weight	code		max T. on glass ta 25°	max T. on glass ta 15°	max load kg	Can be walked on	bears vehicle loads	K	ølm 24V
4w LED white	s. steel	12.00	530990-00	32W	30°	20°	2000	OK	OK	4000	1440lm

Best suited for installation as lighted floor. Incorporated power supply 220-240V 50/60 Hz. Output current, see table.

1832 Quadro LED - Power LED RGB Fullcolor

wattage (350mA)	colour	CLD CTL		W tot	temperature and load				LED (Ta=25°C)		
		weight	code		max T. on glass ta 25°	max T. on glass ta 15°	max load kg	Can be walked on	bears vehicle loads	ølm 350mA	
4,5W LED Fullcolor	s. steel	12.00	530991-00	36W	30°	20°	2000	OK	OK		8 x105lm

Power LED RGB: high density bright LED; small source with multicolor optics.